

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
16 June 2005 (16.06.2005)

PCT

(10) International Publication Number
WO 2005/053875 A1

(51) International Patent Classification⁷: **B21K 1/00**,
1/76, B21J 5/02, 5/12, B62D 3/12, 5/22

(21) International Application Number:
PCT/AU2004/001693

(22) International Filing Date: 3 December 2004 (03.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003906722 4 December 2003 (04.12.2003) AU

(71) Applicant (for all designated States except US): **BISHOP INNOVATION LIMITED** [AU/AU]; 10 Waterloo Road, North Ryde, NSW 2113 (AU).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **DOHMANN, Juer-gen** [DE/AU]; 31 Walker St., Redfern, NSW 2016 (AU). **JAEGGI, Johann, Friederich** [AU/AU]; 3 Hafey Road, Kenthurst, NSW 2156 (AU). **MCLEAN, Lyle, John** [AU/AU]; 103 Pebbly Hill Road, Maraylya, NSW 2765 (AU).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: STEERING RACK MANUFACTURE



(57) Abstract: A die apparatus and method for performing a flashless forging operation to manufacture the toothed portion of a steering rack. The die apparatus comprising first and second die members and at least one punch member, each having a forming surface shaped substantially as the obverse of a portion of said toothed portion, and at least a portion of the forming surface of said first die member being shaped substantially as the obverse of the teeth of said rack. Said first and second die members being moveable towards each other to a closed position thereby partially forging said toothed portion from a blank placed in said die apparatus and forming a substantially closed cavity defined by said forming surfaces, said punch member being adapted to move into said cavity, once said die members are in said closed position, thereby completing said forging operation.

WO 2005/053875 A1